



- Variable temperature range 0°C and +15°C
- Efficient and environmentally-friendly refrigerants
- Forced-air cooling
- White or powder-coated sheet steel housing
- Analogue or digital temperature displays show the actual internal temperature
- highly effective insulation which efficiently prevents the loss of cold air
- LED interior light with a separate switch
- The heavy-duty lock

**Structural specifications**

Internal and external structure data	
External material	steel / white
Door material	glass / steel
Internal material	commercial grade moulded
Shelf grids material	wire shelves plastic-coated
Controller data	
Temperature display	external digital or analogue
Key lock data	
Key lock	standard equipment
Refrigerant gas data	
Type of refrigerant	R 600a FC free

**Model code variations**

Interior volume	Door material	External material	Temperature	Description	Model code				
100			-10...-26°C	100 liters, steel door and white external material	FKB100				
				100 liters, steel door and steel external material	FKB100X				
			0...+15°C	100 liters, steel door, white external material and forced ventilation	FK100				
				100 liters, glass door, white external material and forced ventilation	FK100G				
				100 liters, steel door, steel external material and forced ventilation	FK100X				
				100 liters, glass door, steel external material and forced ventilation	FK100GX				
260			0...+15°C	260 liters, steel door, white external material and forced ventilation	FK260				
				260 liters, glass door, white external material and forced ventilation	FK260G				
				260 liters, steel door, steel external material and forced ventilation	FK260X				
				260 liters, glass door, steel external material and forced ventilation	FK260GX				
				360	glass or steel	white or steel	0...+15°C	360 liters, steel door, white external material and forced ventilation	FK360
								360 liters, glass door, white external material and forced ventilation	FK360G
360 liters, steel door, steel external material and forced ventilation	FK360X								
360 liters, glass door, steel external material and forced ventilation	FK360GX								
440			0...+15°C					440 liters, steel door, white external material and forced ventilation	FK440
								440 liters, glass door, white external material and forced ventilation	FK440G
				440 liters, steel door, steel external material and forced ventilation	FK440X				
				440 liters, glass door, steel external material and forced ventilation	FK440GX				
				540			0...+15°C	540 liters, steel door, white external material and forced ventilation	FK540
								540 liters, glass door, white external material and forced ventilation	FK540G
540 liters, steel door, steel external material and forced ventilation	FK540X								
540 liters, glass door, steel external material and forced ventilation	FK540GX								

**Technical specifications**

	FKB100	FK100	FK260	FK360	FK440	FK540
<b>Model</b>		FK100G	FK260G	FK360G	FK440G	FK540G
		FK100X	FK260X	FK360X	FK440X	FK540X
		FK100GX	FK260GX	FK360GX	FK440GX	FK540GX
<b>Temperature data</b>						
Temperature range [°C]	-10...-26	0...+15	0...+15	0...+15	0...+15	0...+15
<b>Measures</b>						
Net capacity [liters]	133	130	229	320	359	536
External dimensions [WxDxH mm]	600x615x830	600x615x830	600x610x1250	600x610x1640	600x610x1800	750x730x1640
Internal dimensions [WxDxH mm]	474x443x676	440x435x670	470x440x1062	470x440x1452	470x440x1612	600x560x1452
Net weight [Kg]	40	40	55	65	75	85
<b>Controller data</b>						
Type of control	electronic	electronic	analogue	analogue	analogue	analogue
<b>Cooling data</b>						
Cooling system	static	forced air	forced air	forced air	forced air	forced air
Defrost	manual	automatic	automatic	automatic	automatic	automatic
<b>Illumination data</b>						
Interior light	-	LED light only for glass configuration				
<b>Shelf grid data</b>						
Adjustable shelves	4	3	3	4	5	4
Drawers	3	-	-	-	-	-
Baskets	1	-	-	-	-	-
Shelf loading [Kg]	24	45	45	45	45	60
<b>Alarm data</b>						
Warning alarm	Visual and audible	Visual and audible	-	-	-	-
<b>Sound power data</b>						
Sound power level [dB]	45	45	45	45	45	45
<b>Electrical data</b>						
Connection rating [A/W]	0.6/100	1.0/100	1.0/130	1.5/145	1.5/170	1.5/175
Rated Voltage [V]	220/240	220/240	220/240	220/240	220/240	220/240
Power Frequency [Hz]	50	50	50	50	50	50